

HUNDAL



BUILT TO WORK.

BUILT TO LAST.



HUNDAL  
TASKFORCE  
1150

Main dimension	
Overall dimensions	2835*1035*1670mm
Bucket width	1140mm
Bucket capacity	1.14m <sup>3</sup>
Track width	200mm
The maximum lifting height of the upper arm	2155mm
Loading capacity	500KG
Tipping capacity	1100KG
Net weight of the entire vehicle	1780KG
Driving speed	10KM/H
Turning radius	1528mm
Engine & control system	
Engine model	KUBOTA D1105
Fuel/Cooling method	
Engine power	18.2KW
Maximum speed	3000rpm
Torque	DIESEL/WATER COOLING (2200rpm) 71.5Nm
Displacement	1.1L
Fuel consumption	6.1L/h
Lubrication	Gear pump pressure
Main pump control valve	Hydraulic pilot load sensitive
Assistive control valve	Mechanical type
specifications	
Working pressure	0-21Mpa
Cooling system capacity	5.6L
Fuel tank capacity	33L
Engine lubricating oil	5.1L
Capacity of hydraulic oil tank	30L
Hydraulic system oil volume	33L
Flow rate of the walking pump	61.6L/min
The pressure of the walking pump	21Mpa
Working pump flow rate	47.6L/min
Working pump pressure	23Mpa







**With automatic leveling** of bucket, the bucket is always in a balanced state during operation, which is more convenient and faster without additional operation.

